

Continuous louvre walls DucoWall Classic W 50Z

Manufactured by: DUCO Ventilation & Sun Control

DucoWall Classic W 50Z is a louvre wall system that can be placed against a support structure. Quick and easy assembly is possible because of the 'Turn-Click' system. The "Z"-shaped louvre produces a sleek design.

Features:

- **Louvre blades:**
Z-shaped aluminium extrusions clipped into blade holders
 - Blade height: 76 mm
 - Louvre pitch: 65 mm
 - Louvre blade depth: 53 mm
 - Section thickness: minimum 1.5 mm
 - Visual free area: 75 %
 - Physical free area: 52%
- **Support profiles:**
Aluminium extrusions featuring a groove for securing the blade holders
The lightweight support profiles 30/12 and 50/12: fixing directly to underlying structure (without free overhang)
Heavy-duty support profiles 21/50 Multi, 50/50 and 50/125: suitable for free overhang, attached to underlying structure by means of supplied L-profiles
- **Blade holders:** injection-moulded parts made of polyamide PA 6.6 glass-fibre reinforced
- **Recess depth:**
 - Support profile 50/12: 65 mm
 - Support profile 50/50 or 21/50 Multi: 103 mm
 - Support profile 50/125: 178 mm

Surface treatment:

- Anodisation: Qualanod-compliant, coating thickness 15-20µm, standard natural colour (colourless anodisation)
- Powder coating: Qualicoat Seaside type A compliant, minimum average coating thickness 60µm, standard RAL colours 70% gloss
Upon request: other finish coating thicknesses, anodising colours and paint gloss levels, textured paints and specific powder coating product codes

Functional specifications:

- **Flow rate standard version:**
 - K-factor inlet: 23.80
 - K-factor outlet: 12.94
 - C_e coefficient: 0.205
 - C_dcoefficient: 0.278

- Flow rate version "+ options":
 - K-factor inlet: 23.34
 - K-factor outlet: 14.13
 - C_e coefficient: 0.207
 - C_d coefficient: 0.266

- Water repellency standard version:
 - $v = 0.0\text{m/s}$: class B
 - $v = 0.5\text{m/s}$: class C
 - $v = 1.0\text{m/s}$: class C
 - $v = 1,5\text{m/s}$: class C
 - $v = 2.0\text{m/s}$: class D
 - $v = 2.5\text{m/s}$: class D
 - $v = 2.0\text{m/s}$: class D
 - $v = 2.5\text{m/s}$: class D

- Water repellency version "+ options":
 - $v = 0.0\text{m/s}$: class A
 - $v = 0.5\text{m/s}$: class B
 - $v = 1.0\text{m/s}$: class B
 - $v = 1,5\text{m/s}$: class C
 - $v = 2.0\text{m/s}$: class C
 - $v = 2.5\text{m/s}$: class D
 - $v = 2.0\text{m/s}$: class D
 - $v = 2.5\text{m/s}$: class D

Complies with or tested in accordance with the following standards:

- Qualicoat Seaside type A (if painted finish)
- Qualanod (if anodised finish)
- EN 573 - EN AW-6063 T66 and EN AW-6060 T66: aluminium alloy & hardening
- EN 13030: water resistance and determination of C_e and C_d coefficients
- EN 1990, EN 1991, EN 1999: strength calculations

Optional burglary protection

Continuous louvre wall can optionally be provided with wire mesh for RC2 burglar resistance. Class 2 (EN1627:2011 & NEN 5096:2012+A1:2015)